


Project Name:	Notes:	Date:	Type:
---------------	--------	-------	-------



**54W**  
Wattage

(Replaces 175W HID/MH)

**PHOTOMETRY**



UNIT: cd

- C0/180, 2.70
- C90/270, 2.68

Average Beam Angle (50%) : 287.8 degree

**FEATURES**

- High lumen LED bulb for commercial or industrial applications
- For outdoor & indoor use
- Base up, down or horizontal operation
- Replacing HID, CFL, and Incandescent lamps
- Ballast by-pass - direct wire only
- UL approved for enclosed fixtures

**DISSIPATION**

- Passive cooling via aluminum
- More reliability and less failure

**CONSTRUCTION**

- Power pack is made of aluminum
- Better for heat dissipation
- Enough space for components on the PCB

**TECHNICAL SPECIFICATION**

WATTAGE	54W
LUMENS	6,750 lumens
EFFICACY	125 lm/W
LAMP BASE	E26 (Mogul base EX39 adapter included)
VOLTAGE	100-277V
POWER FREQUENCY	50/60 Hz
CCT	5000K
CRI	Ra>80
OPERATING TEMP.	-40°F ~ 113°F
OPERATING HUMIDITY	20% - 70% RH
STORAGE TEMP.	-40°F ~ 176°F
STORAGE HUMIDITY	10% - 75% RH
IP RATING	IP64 for damp locations
POWER FACTOR	>0.9
UNIT SIZE	3.35" x 9.09"



LM79 & LM80  
Tested