



Project Name:	Notes:	Date:	Type:
---------------	--------	-------	-------



75W
Wattage
(Replaces 200W HID/MH)

PHOTOMETRY



UNIT: cd
 — C0/180, 3.24
 — C90/270, 3.27

Average Beam Angle (50%) : 284.5 degree

FEATURES

- High lumen LED bulb for commercial or industrial applications
- For outdoor & indoor use
- Base up, down or horizontal operation
- Replacing HID, CFL, and Incandescent lamps
- Ballast by-pass - direct wire only
- UL approved for enclosed fixtures

DISSIPATION

- Passive cooling via aluminum
- More reliability and less failure

CONSTRUCTION

- Power pack is made of aluminum
- Better for heat dissipation
- Enough space for components on the PCB

TECHNICAL SPECIFICATION

WATTAGE	75W
LUMENS	9,375 lumens
EFFICACY	125 lm/W
LAMP BASE	EX39
VOLTAGE	100-277V
POWER FREQUENCY	50/60 Hz
CCT	5000K
CRI	Ra>80
OPERATING TEMP.	-40°F ~ 113°F
OPERATING HUMIDITY	20% - 70% RH
STORAGE TEMP.	-40°F ~ 176°F
STORAGE HUMIDITY	10% - 75% RH
IP RATING	IP64 for damp locations
POWER FACTOR	>0.9
UNIT SIZE	5.12" x 9.96"



LM79 & LM80
Tested