

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

The PT-EXL-C-SLM Series is the category leader in emergency lighting featuring adjustable, dual head lights, 90-minute power outage uptime, backlit red chevrons (single or double), and a polycarbonate housing that is universally mountable. The EXL-C series is UL924, UL damp location, NFPA 101, NEC/OSHA, Title 20 compliant and adheres to the majority of state and local codes for indoor exit and emergency lighting solutions.

Ideal use for commercial buildings, industrial facilities, entryways, stairways, and hallways.



CONSTRUCTION

Market standard mold consisting of thermoplastic ABS housing with UL 94V-0 flame rating. Field adjustable for single or dual face in red color only. 3.3W LED lamp heads for emergency mode.

ELECTRICAL

Dual voltage operation with 120V/277VAC and input watt of 3.3W. Includes built-in 3.6V1000mAh Ni-MH battery with a 90-minute runtime and 24 hour charge time. Test switch and charge indicator.

MOUNTING

The universal J-Box mounting pattern supports quick installation time. Mount directly on a wall or ceiling.

ENERGY SAVINGS

LED emergency lights may reduce energy consumption up to 85% and lower overall maintenance costs.

LISTING

UL Listed, RoHS


WARRANTY

5 year limited warranty on electrical parts and housing.
3 year limited warranty on battery.

TECHNICAL SPECIFICATION

INPUT WATT	3.3W
LUMENS	200 lm
VOLTAGE	Dual Voltage 120V-277V
BATTERY TYPE	3.6V1000mAh Ni-MH
EM RUN TIME	90 mins
CHARGING TIME	24 hrs
WORKING TEMPERATURE	32°F ~ 104°F
IP RATING	Indoor Damp Location

DIMENSION



ORDERING SAMPLE: PT-EXL-C-SLM

Series	Style/Shape	No. of Face	Finish	Mounting
PT-EXL-C Exit and Emergency Lighting Combo	SLM (SlimLED Lamp)	Single or double face (universal)	White	Universal mounting (Ceiling, Wall)