

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

Portor's second generation PT-WPM2 series combines economical and security solution for outdoor perimeter and building facades. The LED driver is mounted in direct contact with the casting to promote low operating temperature and long life.

Ideal use for warehouses, walkways, building entry ways, parking lots, retail exteriors and shopping malls.

DUSK TO DAWN



CONSTRUCTION

Die-Cast aluminum housing. Sealed by a silicone ring that makes the fixture waterproof, internal level ensures installation is horizontal.

DUSK TO DAWN

Internal photocell design which can automatically turn on at dusk and turn off at dawn for up to 70% of energy saving.

OPTICAL SYSTEM

PC lens designed to reduce glare and improve over-all light distribution through precision formed LED optics.

ELECTRICAL

Luminaire is built with the highest quality driver that is universal voltage (120-277V), uses highly-efficient LED packages to ensure cool temperatures for long lasting life span.

CONTROLS

Options available for occupancy sensors with daylight harvesting function, pre-installed photocell.

LISTING

UL Listed, DLC Premium Listed, IP65 Rated, ROHS

LIFESPAN


L70 > 50,000 hours

TECHNICAL SPECIFICATION

CCT	3000K/4000K/5000K
CRI	80+
DIMMING	0-10V dimming
VOLTAGE	120V-277V
POWER FREQUENCY	50/60 Hz
POWER FACTOR	>0.9
THD	≤20%
WORKING TEMPERATURE	-40°F ~ 113°F
IP RATING	IP65 Wet Location
WARRANTY	5 year limited (Standard)







DIMENSION



DIMENSION	PT-WPM2 Series
A	5.8"
B	8.6"
C	3"
Net Weight	2 lbs
Gross Weight	2.5 lbs

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

ORDERING SAMPLE: **PT-WPM2-30W-3CCT-MS-WP3-MSS-RC-100**

PT-WPM2		-		-	3CCT		-		-	
Fixture			Controls/Sensors ³							
Series	Wattage	CCT	Analog Sensors		Remote					
PT-WPM2	15W	3CCT (30K/40K/50K)	__ Blank		__ Blank					
	20W									
	30W		MS-WP3 Microwave Motion Sensor (100V-277V)		MSS-RC-100 Remote Control					
Add-On ³		Mounting	Photocell	Fixture Add-on ³		Other Option				
EM Battery		Wall Mount	Integrated Photocell	Transformer ²		Warranty				
__ Blank		_ Blank (Wall mount)	__ Blank	__ Blank		__ Blank (5 year standard)				
						7YR 7-year Limited Warranty				
PT-EMA-8W 8W AC Emergency Battery Pack (Remote installation)				PT-SDT-325 325 VA Step down Transformer (Remote installation)		10YR 10-year Limited Warranty				

² **TRANSFORMER**




PT-SDT-325 is a step-down auto-transformer designed to convert high voltage, low current power into low voltage, high current power. It has a maximum power rating of 325VA, which makes it suitable for use in a variety of applications, such as electrical power transmission, distribution, and electronic devices. Remote installation.

³ **SOLD SEPARATELY**

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

LUMEN PACKAGES

(Delivered lumens are based on the actual IES results)

CATALOG NUMBER	WATTAGE	CCT	DELIVERED LUMENS	EFFICACY (LM/W)	DLC ID
 PT-WPM2-15W-3CCT	15W	3000K	2,041	136	PLMZ5EXRZGTD
		4000K	2,129	141	
		5000K	2,038	135	
CATALOG NUMBER	WATTAGE	CCT	DELIVERED LUMENS	EFFICACY (LM/W)	DLC ID
 PT-WPM2-20W-3CCT	20W	3000K	2,647	132	PL31A99KX4XF
		4000K	2,693	134	
		5000K	2,538	126	
CATALOG NUMBER	WATTAGE	CCT	DELIVERED LUMENS	EFFICACY (LM/W)	DLC ID
 PT-WPM2-30W-3CCT	30w	3000K	3,994	133	PL8SDT04ZZ44
		4000K	4,055	135	
		5000K	3,734	124	



WHAT'S IN THE BOX?

- Fixture
- Installation sheet

QTY/CARTON

1
PIECES