



# PT-DLS2-R-8I-18W-5CCT

8" Round LED Slim Recessed Downlight with CCT Selector

Project Name:

Notes:



3500K, 4000K, or 5000K. Ideal for soffits, drop ceilings, closets, attics, hallways, bathrooms, kitchens, basements, entry ways, porches (covered ceiling only), garages, stairwells, corridors, nursing/ retirement homes, condos, elevators, apartments, and any other small areas with

No can or housing needed! Install directly into ceilings with 2" clearance. Portor's slim round profile residential downlights are taking the market by storm! Available in 8" and featuring color tunable technology that lets the user choose between 2700K, 3000K,

## FEATURES

limited space.

- Edge-lit technology, with no glare or dark spots
- Instant-on
- Ultra slim design, 1" thickness
- Integrated LED fixtures
- · LED technology fits anywhere you need general light source
- IC rated for direct contact with insulation
- Perfect solution where joists or duct work would normally prevent recessed installation
- Damp location rated for soffit applications
- Install J-Box in ceiling beam, and insert light right into drywall opening

#### DIMMING

Triac dimmable down to 100%-10%. Compatible with most major brands of dimmers.

#### LISTING

ETL Listed, FCC, RoHS, CE & Energy Star Listed



WATTAGE	DELIVERED LUMENS	EFFICACY	
18W	1442 @ 2700K	80 lm/W	
	1488 @ 3000K	82 lm/W	
	1504 @ 3500K	83 lm/W	
	1474 @ 4000K	81 lm/W	
	1409 @ 5000K	78 lm/W	

#### **TECHNICAL SPECIFICATION**

WATTAGE	18W		
VOLTAGE	120V		
POWER FREQUENCY	50/60 Hz		
CCT	2700K/3000K/3500K/4000K/5000K		
CRI	90		
BEAM ANGLE	120°		
RATING	Suitable for damp locations		
DIMMABLE	Triac dimming		
POWER FACTOR	>0.9		
WARRANTY	5 year limited		

MODEL NUMBER(S)						
MODEL#	WATTS	LUMENS	LM/WATT	CCT	CRI	VOLTAGE
PT-DLS2-R-8I-18W-5CCT	18W	1474 ( <b>at 4000K)</b>	81	2700K/3000K/3500K/ 4000K/5000K	90	120V





8" Round LED Slim Recessed Downlight with CCT Selector

Date:







### DIMENSION



(Cut-out: 8")

#### **COMPATIBLE DIMMERS**

LUTRON*	LEVITON*	LEGRAND
• CT-600P	• RNL06	ADTP70TU
<ul> <li>DVLC-153P</li> </ul>	• 6672	
<ul> <li>MSCL-0P153M</li> </ul>	• 6674	
PD-6WCL	• IPL06	
• MACL-153M/MA-R	• DLS06	
• TG-600PR-WH	<ul> <li>SELV-300P-WH</li> </ul>	
• S-600PR-WH	• VP106-1LZ	
<ul> <li>CTCL-153PDH-WH</li> </ul>		
<ul> <li>TGCL-153PH-LA</li> </ul>		
• SLV-600P-AL		
• DV-600PR-WH		
<ul> <li>SCL-153PH-WH</li> </ul>		

\*For more details, please visit company's website



## MOUNTING OPTION



**UNI-DLS-R** 4"/6" Universal Slim LED Housing for New Construction



RP-DLS-8I 8" LED Rough plate