

2' x 4' LED Back-Lit Flat Panel with Color Selectable and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Туре:
Portor's New Generation BLP4 series produce industry-lea energy savings and continuous dimming. The compact, sl				
glare free lumen output. Perfect application for retail stores, schools, offices, mark	ets and restaurant.			
		SELECTABLE		

CONSTRUCTION

Durable solid frame, prefabricated paint with matte white finished. Slim profile design. Integrated T-Bar mounting clips built in onto the fixture. Easy installation

ELECTRICAL

Luminaire is built with the highest quality driver that is Universal Voltage (120V-27V), uses long lasting, highly-efficient LED packages.

DRIVER

Driver is fixed on the back of the panel or side to prevent mis-handling during shipment.

OPTICAL SYSTEM

Back-lit optics produces uniform light output, diffuser lens reduces glare and improve overall energy efficiency.

DIMMING

Continuous dimming (0-10V) comes standard.

ENERGY SAVINGS

Over 50% energy savings than traditionally fluorescent fixtures, low heat productions requires less maintenance and operation cost.

S

DIMMABLE

LISTING

UL Listed, DLC Pemium Listed, RoHS

WARRANTY

5 Years Limited Warranty, Rated for 50,000 hours (See Warranty documentation for details).

WATTAGE	DELIVERED LUMENS	EFFICACY
30W	3,990	133 lm/W
40W	5,200	130 lm/W
50W	6,350	127 lm/W

PT-BLP4-24-3CP

Based on 5000K, 80 CRI. Actual lumens may vary.

TECHNICAL SPECIFICATION

CCT	3500K/4000K/5000K
CRI	80+
DIMMABLE	0-10V dimming
VOLTAGE	120V-277V
POWER FREQUENCY	50/60 Hz
POWER FACTOR	>0.9
THD	≤20%
DRIVER EFFICIENCY	>85%
RATING	IP40, Suitable for damp locations
WARRANTY	5 year limited

ORDERING SAMPLE:	-	-		-
Series	Size	CCT/Wattage	Accessories/Options	
PT-BLP4	24 - (2' x 4')	3CP	EM Battery	Other
LED Back-Lit Flat Panel with CCT and Wattage Selector Series		(CCT: 3500K/4000K/5000K) (Wattage: 30W/40W/50W)	Blank EM	Blank SMK-BLP-24 FK-24






PT-BLP4-24-3CP


2' x 4' LED Back-Lit Flat Panel with Color Selectable and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Туре:



Maintenance-free optical module sealed for life; no internal cleaning required.

DIMENSION



EM BATTERY OPTION



EM Low Voltage EM Battery

OTHER



SMK-BLP-24 Surface mount kit for the 2x4 panel



FK-24 Flange kit for the 2x4 panel