


Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

The PT-VS-WD Vapor-Seal series offers an industry-leading performance with deep energy savings and continuous dimming. This fixture is manufactured and designed using a gasketed enclosure to protect against dust, humidity and liquid spray. Easy installation for both surface-mount and suspended mount.

Perfect application for factories, tunnels, car washes, laboratories, cold storage, food processing and for vessels.



CONSTRUCTION

Polycarbonate housing, frosted lens, and stain-less clips offer protection against dust, humidity and water spray. Environmental-friendly powder coat painted reflector. Compact, slick profile design makes it easy for installation.

ELECTRICAL

Luminaire is built with the highest quality driver that is universal voltage 120-277V 50/60Hz, Class P and Class 2 with 2kV Surge Protection, uses highly-efficient LED packages to ensure cool temperatures for long lasting life span.

OPTICAL SYSTEM

Long life and high-efficiency surface mount LEDs. 100,000-hour LED lifespan based on LM-80 results and TM-21 calculations.

DIMMING

Continuous dimming (0-10V) comes standard. Compatible with dimmers, sensors and controls for deeper energy-savings.

MOUNTING

V-hooks/surface mount (included), 45° corner mount, and junction box.

ENERGY SAVINGS

Over 50% energy savings than traditionally fluorescent fixtures, low heat productions requires less maintenance and operation cost.

LISTING

UL Listed, IP66 Rated, NEMA 4X, NSF, RoHS

WARRANTY

5 year Limited Warranty

WATTAGE	DELIVERED LUMENS	EFFICACY
4' 150W/175W/200W	6,650 @ 5000K	133 lm/W

Based on max wattage and 3500K setting. Actual lumens may vary.

TECHNICAL SPECIFICATION

CCT	3500K/4000K/5000K
CRI	80+
DIMMABLE	0-10V dimming
BEAM ANGLE	110°
VOLTAGE	120V-277V
POWER FREQUENCY	50/60 Hz
POWER FACTOR	>0.9
THD	≤10%
TEMPERATURE RATED	-40°F ~ 122°F
IP RATING	IP66
WARRANTY	5 year limited




ORDERING SAMPLE: - - - - -


Series	Wattage	Feature	CCT	Mounting	EM Battery	Options
PT-VS-WD Modest Style Vapor-Seal Luminaire	4FT - 4' (30W/40W/50W)	HW High Wattage	3CP (3500K/4000K/5000K)	V-Hooks Surface Mount	EM Battery	Motion Sensor

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------


DIMENSION



MOUNTING



SM
Surface mount
(Included)



V-HOOK
Suspended Mount (Included)



A-CBL
Aircraft Cable
(Chain or cable sold separate)

MOTION SENSORS



MS-MW
Motion Sensor



MSH-RC2
Indoor Sensor Remote Programmer
(Needed to program the motion sensor)

EM BATTERY OPTION



PT-EMN SERIES
Low Voltage EM
Battery Back-up