

PT-DLG-R-4I-12W-3CCT

4" LED Recessed Round Gimbal with Multiple CCT

Catalog Number: Project Name: Note: Date: Type:

DESCRIPTION

With color tuning technology, and 30° tilting/360° rotating capability, Portor's 4" gimbal downlights make accent, spot lighting, and wall washing so easy!

Gimbal downlights are ideal for both commercial and residential lighting, and are optimal for sloped ceilings, wall washing and general purpose lighting.



TUNABLE 3-1 CCT SELECTOR



CONSTRUCTION

Aluminum die-cast body and trim with architectural white finish. Designed for new construction, remodel or retrofit. Standard gasket included to ensure proper seal. No housing required, installs directly into the ceiling.

FI FCTRICAL

Luminaire is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than traditional lamps. Low heat production requires less air-conditioning requirements, further increasing energy cost savings.

DIMMING

Triac dimmable down to 5%. Compatible with most major brands of dimmers.

LISTING

Energy Star Listed, ETL Listed, RoHS

TECHNICAL SPECIFICATION

WATTAGE	12W			
LUMENS	800 lumens			
EFFICACY	67 lm/W			
VOLTAGE	120V			
POWER FREQUENCY	50/60 Hz			
CCT	3000K 4000K 5000K			
CRI	97			
IP RATING	For wet locations			
DIMMABLE	Triac dimming			
POWER FACTOR	>0.9			
WARRANTY	5 year limited			
	:			











ORDERING SAMPLE: PT-DLG-R-4I-12W-3CCT

Series	Watts	Lumens	Lms/Watt	ССТ	CRI	Voltage
PT-DLG-R-4I-12W-3CCT	12W	800 @4000K	67	3000K/4000K/5000K	97	120V





PT-DLG-R-4I-12W-3CCT

4" LED Recessed Round Gimbal with Multiple CCT

Catalog Number: Project Name: Note: Date: Type:



MOUNTING OPTIONS



UNI-DLS 4"/6" Universal Housing for New Construction



RP-DLS-4I 4" Rough plate

QTY/CARTON



Sealing gasket standard

DIMENSION

