

Project Name: Notes: Date: Type:










PHOTOMETRY



Average Beam Angle (50%): 287.8 degree

FEATURES

- · High lumen LED bulb for commercial or industrial applications
- · For outdoor & indoor use
- · Base up, down or horizontal operation
- · Replacing HID, CFL, and Incandescent lamps
- · Ballast by-pass direct wire only
- · UL approved for enclosed fixtures

DISSIPATION

- · Passive cooling via aluminum
- · More reliability and less failure

CONSTRUCTION

- · Power pack is made of aluminum
- · Better for heat dissipation
- · Enough space for components on the PCB

TECHNICAL SPECIFICATION

WATTAGE	54W
LUMENS	6,750 lumens
EFFICACY	125 lm/W
LAMP BASE	E26 (Mogul base EX39 adapter included)
VOLTAGE	100-277V
POWER FREQUENCY	50/60 Hz
CCT	5000K
CRI	Ra>80
OPERATING TEMP.	-40°F ~ 113°F
OPERATING HUMIDITY	20% - 70% RH
STORAGE TEMP.	-40°F ~ 176°F
STORAGE HUMIDITY	10% - 75% RH
IP RATING	IP64 for damp locations
POWER FACTOR	>0.9
UNIT SIZE	3.35" x 9.09"









