

CONSTRUCTION

ELECTRICAL

MOUNTING

LISTING

WARRANTY

5 year Limited Warranty

**ENERGY SAVINGS** 

rugged for outdoor harsh conditions.

Anchor bolt included, require assembly.

maintenance and operation cost.

UL Listed, IP65 rated, DLC Listed

# PT-ABL-R-BTP-C-3CP

Architectural Bevel-top Cone Style Bollard with CCT and Wattage Selector

 Catalog Number:
 Project Name:
 Note:
 Date:
 Type:

 Portor Lighting elevates your outdoor spaces with our Bollard Style Lighting. A perfect blend of functionality and aesthetics our bollard lights bring safety ambiance and
 IP65

blend of functionality and aesthetics, our bollard lights bring safety, ambiance, and architectural charm. Experience modern illumination designed to enhance your surroundings, guiding your way with a touch of elegance.

Ideal use for walkways, entrance ways, drives and other small-area lighting applications where low mounting heights are desirable.

Die-cast aluminum body combined with state of the art heat dissipation. Waterproof, built

Built with the highest quality, long lasting Universal Voltage driver 120V-27V.

Over 70% energy savings than traditional fixtures, low heat productions requires less

# WATTAGE DELIVERED LUMENS EFFICACY 14W 1960 140 lm/W 19W 2300 140 lm/W 24W 3360 140 lm/W

Based on 3000K setting. Actual lumens may vary.

#### **TECHNICAL SPECIFICATION**

ECTOR

CCT	3000K/4000K/5000K
CRI	70+
DIMMABLE	0-10V dimmable
VOLTAGE	120V-277V
POWER FACTOR	>0.9
SURGE PROTECTOR	4KV
WORKING TEMPERATURE	-40°F ~ 113°F
IP RATING	IP65 Wet Location
WARRANTY	5 year limited



## ORDERINGSAMPLE: PT-ABL-R-DTP-C-3CP

Complete Series	Shape	Тор	Style	CCT/Wattage	Lumen	Lumen/Watt	Finish
PT-ABL Architectural Bollard	R (Round)	BTP (Bevel Top)	<b>C</b> (Column)	<b>3CP</b> (30K/40K/50K) (14W/19W/24W)	1960/2300/3360 Lm	140Lm/W	Bronze






## PT-ABL-R-BTP-C-3CP

Architectural Bevel-top Cone Style Bollard with CCT and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Туре:
-----------------	---------------	-------	-------	-------

### DIMENSION





Anchor Bolt Require assembly (Included)



PIECES

CATALOG NUMBER	WATTAGE	DELIVERED LUMENS	EFFICACY	DLC PRODUCT ID	CLASSIFICATION	
PT-ABL-R-BTP-L-3CP	14W	1960			PREMIUM	
	19W	2300	140 lm/W	S-ROKAHW		
	24W	3360				

Based on 3000K setting. Actual lumens may vary.

