

PT-TRO-HO-22-3CP

2' x 2' High Output Center Basket Troffer with CCT and Wattage Selector

	3 1				5
Catalog Number:	Project Name:	Note	e:	Date:	Type:
Portor's TRO-HO is High-Output luminai be programmed with a CCT of 3500K, need to stock multiple color temperatu Ideal use for office spaces , walkways, s centers, hospitality and health care inc	4000K, or 5000K, eliminating the ures.				
HIGH OUTPUT T	ROFFER	3CCT 	WATTAGE SELECTOR		

CONSTRUCTION

Constructed of one-piece ribbed unitized housing and corners that interlock, preventing damage to luminaire. All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation.

ELECTRICAL

Luminaire is built with the highest quality 120-277VAC drivers.

OPTICAL SYSTEM

Designed to reduce glare and improve light distribution through precision formed lens optics.

DIMMING

0-10V dimmable standard

CONTROLS

Option available for dimmers and occupancy sensors (consult factory) to maximize energy savings.

LISTING

UL Listed, RoHS

WARRANTY

5 Years Limited Warranty











WATTAGE	DELIVERED LUMENS	EFFICACY
30W	3,991	
35W	4,594	up to 146 lm/W
40W	5,162	

Based on 4000K setting. Actual lumens may vary.

TECHNICAL SPECIFICATION

1500K/4000K/5000K
3500K/4000K/5000K
30
0-10V dimmable
20°
20V-277V, 50/60 Hz
0.9
20%
40°F ~ 122°F
Suitable for damp locations
year limited
S-01LZ7X
3)

ORDERING SAMPLE:	-		-		
Series	Size	CCT/Wattage	Accessories/Options		
PT-TRO-HO	22 (2' × 2')	3CP	Sensor	EM Battery	
High Output Troffer	` '	(3500K/4000K/5000K) (25W/30W/35W)	MS or blank	EM or blank	






PT-TRO-HO-22-3CP

2' x 2' High Output Center Basket Troffer with CCT and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Type:

DIMENSION









MOTION SENSOR



MS Motion Sensor

OPTIONS



EM LED Emergency Driver

MOUNTING KIT



SMK-TRO-22 2'x2' Troffer Surface Mount Kit



FK-22 2'x2' Flange Kit