

Recessed Commercial Grade Downlight with CCT and Wattage Selector

Portor's second generation commercial grade recessed downlight is wattage and color selectable which can be programmed with a CCT of 2700K, 3000K, 3500K, 4000K, or 5000K, eliminating the need to stock multiple color temperatures.

TECHNICAL SPECIFICATION

APERTURE	4" / 6" / 8" 10"
CCT	2700K 3000K 3500K 4000K 5000K
CRI	96
DIMMABLE	0-10V, 5-100% smooth dimming
BEAM ANGLE	100°
VOLTAGE	120V-277V
POWER FREQUENCY	50/60 Hz
POWER FACTOR	>0.9
RATING	Suitable for wet location
WARRANTY	5 year limited



WATTAGE
SELECTOR

Direct Mounting

NO RECESSED HOUSING NEEDED

FOR RETROFIT OR NEW CONSTRUCTION INSTALLATION

20" WHIP INCLUDED



CATALOG NUMBER	WATTAGE	DELIVERED LUMENS	EFFICACY	Specs
Aperture 4"  PT-CDL2-4I-5C3P	6W	747 @ 4000K	up to 112 lm/W	 SCAN FOR COMPLETE SPECS.
	9W	1,014 @ 4000K		
	12W	1,285 @ 4000K		
Aperture 6"  PT-CDL2-6I-5C3P	12W	1,045 @ 4000K	up to 104 lm/W	 SCAN FOR COMPLETE SPECS.
	17W	1,484 @ 4000K		
	22W	1,790 @ 4000K		
Aperture 8"  PT-CDL2-8I-5C3P	17W	1,493 @ 4000K	up to 86 lm/W	 SCAN FOR COMPLETE SPECS.
	24W	2,084 @ 4000K		
	30W	2,240 @ 4000K		
Aperture 10"  PT-CDL2-10I-5C3P	22W	2,006 @ 4000K	up to 86 lm/W	 SCAN FOR COMPLETE SPECS.
	30W	2,583 @ 4000K		
	38W	3,199 @ 4000K		