

LED BACK-LIT FLAT PANEL WITH WATTAGE SELECTOR AND COLOR TUNABLE

PORTOR
LIGHTING

IN STOCK

Portor's LED back-lit flat panel is color tunable/wattage selector, and can be programmed with a CCT of 3500K, 4000K, or 5000K, eliminating the need to stock multiple color temperatures. Commercial grade luminaire utilizing a LED optical system to achieve superior performance and provides high uniformity, excellent efficiency and reduced glare in T-grid ceiling applications.

Ideal use for offices, conference rooms, schools/campuses, retail stores and the health care industry.

**WATTAGE
3W
SELECTOR** **3 CCT
SELECTABLE
35K > 40K >**

2' X 4'

PT-BLP1-24-55W-3CCT

WATTAGE

40W / 50W / 55W

LUMENS

5,000 / 6,250 / 6,875

CCT

3500K / 4000K / 5000K

2' X 2'

PT-BLP1-22-40W-3CCT

WATTAGE

20W / 30W / 40W

LUMENS

2,500 / 3,750 / 5,000

CCT

3500K / 4000K / 5000K

1' X 4'

PT-BLP1-14-30W-3CCT

WATTAGE

20W / 25W / 30W

LUMENS

2,500 / 3,125 / 3,750

CCT

3500K / 4000K / 5000K



RoHS
COMPLIANT



50,000
Life Hours

CONSTRUCTION

Unlike previous back-lit panels, ours achieves the same, or lower depth as standard edge-lit panel. The frame is made of high-grade aluminum, and the back cover of the housing is zinc-coated iron. The LED driver is mounted in direct contact with the casting to promote low operating temperature and long life. Super lightweight, saving money on shipping costs.

- Efficacy: **UP TO 125 LM/W** • Input Voltage: **120V** • Distribution Angle: **120°** •
- CRI: **80** • Dimmable: **0-10V DIMMING STANDARD** • Life span: **50,000 HRS** • Warranty: **5 YEAR LIMITED** •

PORTOR
LIGHTING
www.portorlighting.com

A LED Lighting Manufacturer

1136 S. Vail Ave., Montebello, CA 90640
Tel: 323-516-6458 • Email: info@portorindustry.com

Specification subject to
change without notice.