

**IN STOCK**

**PORTOR**  
LIGHTING

# WE GOT POLES!

A removable plastic pole cap is provided if the pole is drilled for attaching light fixtures. The drill pattern and drill orientation needs to be provided by the customer unless energy light fixtures are used for the project. If a tenon option is selected, a steel tenon will be provided. A 2-3/8" diameter tenon with a 4" length is standard; however, the customer needs to confirm the appropriate tenon size required for the project.

## SQUARE STEEL STRAIGHT POLE


### INCLUDED:



Pole Cap Cover



Base Cover



4-Anchor Bolts

EPA LOAD INFORMATION									
BASE MODEL	MOUNTING HEIGHT	80 MPH W/ 1.3 GUST		90 MPH W/ 1.3 GUST		100 MPH W/ 1.3 GUST		110 MPH W/ 1.3 GUST	
		Max. EPA (SQ FT)	Max. Weight (LBS)	Max. EPA (SQ FT)	Max. Weight (LBS)	Max. EPA (SQ FT)	Max. Weight (LBS)	Max. EPA (SQ FT)	Max. Weight (LBS)
PT-SSP-S-4I	10FT	30.6	765	20.0	500	16.0	400	13.0	325
	12FT	24.4	610	16.0	400	13.0	325	10.0	250
	14FT	19.9	498	13.5	338	10.0	250	7.5	188
	15FT	15.9	398	10.5	263	7.5	188	5.5	138
	16FT	15.9	398	10.5	263	7.5	188	5.5	138
	18FT	12.6	315	8.0	200	5.5	138	4.0	100
	20FT	9.6	240	6.0	150	4.0	100	2.5	63
	25FT	4.8	150	2.6	100	1	50	-	-

(For desired finish color, please inquire for price and availability.)

*\*Will-call only*

PLEASE ASK YOUR LOCAL REPS FOR MORE INFORMATION or VISIT OUR WEBSITE: [WWW.PORTORLIGHTING.COM](http://WWW.PORTORLIGHTING.COM)

**PORTOR**  
LIGHTING  
[www.portorlighting.com](http://www.portorlighting.com)

1136 S. Vail Ave., Montebello, CA 90640  
Tel: 323-516-6458 • Email: [info@portorindustry.com](mailto:info@portorindustry.com)

Specification subject to change without notice.