

High Output Round High Bay with CCT and Wattage Selector

11" / 13"
..... DIAMETER



Premium quality provides excellent solution for high-ceiling mount applications, especially in warehouses, storage facilities, retail spaces, gymnasiums, and convention centers.



TECHNICAL SPECIFICATION

| | |
|--------------|-----------------------|
| CCT | 3500K/4000K/5000K |
| CRI | 80 |
| DIMMABLE | 0-10V dimmable |
| BEAM ANGLE | 90° |
| VOLTAGE | 120V - 277V, 50/60 Hz |
| IP RATING | IP65 Wet Location |
| FINISH COLOR | Black, White |
| WARRANTY | 5 year limited |



| CATALOG NUMBER | WATTAGE | DELIVERED LUMENS | EFFICACY | Specs |
|--|---------|------------------|----------|---|
|  PT-RHB-11D-3CP | 100W | 14668 @ 3000K | 147 lm/W |  SCAN ME, FOR COMPLETE SPECS. |
| | | 15848 @ 4000K | 164 lm/W | |
| | | 15039 @ 5000K | 151 lm/W | |
| | 120W | 16726 @ 3000K | 140 lm/W | |
| | | 18484 @ 4000K | 160 lm/W | |
| | | 17510 @ 5000K | 146 lm/W | |
| | 150W | 20005 @ 3000K | 132 lm/W | |
| | | 22314 @ 4000K | 153 lm/W | |
| | | 21236 @ 5000K | 139 lm/W | |
|  PT-RHB-13D-3CP | 180W | 25233 @ 3000K | 140 lm/W |  SCAN ME, FOR COMPLETE SPECS. |
| | | 28218 @ 4000K | 163 lm/W | |
| | | 26669 @ 5000K | 148 lm/W | |
| | 200W | 28137 @ 3000K | 140 lm/W | |
| | | 31094 @ 4000K | 161 lm/W | |
| | | 29318 @ 5000K | 147 lm/W | |
| | 240W | 33477 @ 3000K | 134 lm/W | |
| | | 37943 @ 4000K | 162 lm/W | |
| | | 33840 @ 5000K | 139 lm/W | |