

PT-BLP-9 Series

Back-Lit Flat Panel with Color and Wattage Selector

Portor's 9th Generation BLP series produce industry-leading performance with deep energy savings and continuous dimming. The compact, slick profile produces uniform and glare free lumen output.

Perfect application for retail stores, schools, offices, markets and restaurant.

2' X 4'

CONSTRUCTION

Constructed with a cold-rolled steel and extruded aluminum frame, finished with a durable matte white coating. Features a sleek, slim profile design with integrated T-bar mounting clips built directly into the fixture for easy installation.

OPTICS

The back-lit Frosted Polystyrene lens ensure uniform light distribution, while the diffuser lens minimizes glare and enhances overall energy efficiency.

ELECTRICAL

Luminaire is built with the highest quality driver that is Universal Voltage (120V-27V). Long life, high-efficacy, micro-power LEDs. Continuous dimming (0-10V) comes standard.

MOUNTING

Recessed ceiling mount ready (default). Surface mount and suspension mount with optional accessories.

CONTROLS

Options available for occupancy sensors with daylight harvesting function, TEELIO Bluetooth lighting controls, and Lutron AWN.

LISTING

UL Listed, DLC Premium Listed, IC rated

LIFESPAN

L70 > 100,000 hours

TECHNICAL SPECIFICATION

CCT	3500K/4000K/5000K
CRI	80+
DIMMING	1-10V dimming
VOLTAGE	120V-277V
POWER FREQUENCY	50/60 Hz
CURRENT	0.9 - 0.33A
POWER FACTOR	>0.9
THD	≤20%
WORKING TEMPERATURE	-4°F ~ 122°F
IP RATING	IP40, For damp location
WARRANTY	5 year limited (Standard)
















DIMENSION



CATALOG NO.	PT-BLP-24-40-3CP-9	PT-BLP-22-40-3CP-9
Α	47.8"	23.7"
В	23.7"	23.7"
С	1.5"	1.5"
Net Weight	7.41 lbs	3.91 lbs
Gross Weight	8.84 lbs	4.77 lbs





PT-BLP -

PT-BLP-9 Series

Back-Lit Flat Panel with Color and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Туре:


ORDERING SAMPLE: PT-BLP-24-3CP-9-PT-BTC-6-PT-BTN-PT-EMG-8-MC-5W-SC-6F


I I DLI		301	9			
	Fixture					
Series	Size	CCT/Wattage	Generation			
DT DI D	22 (2′ X 2′)	3CP (25W/30W/40W) (35K/40K/50K)	9 (9 Generation)			
PT-BLP	24 (2' X 4')	3CP (25W/30W/40W) (35K/40K/50K)	9 (9 Generation)			

3CP

			-
	Controls/Sensors ³		Add-0n ³
TEELIO ¹	Analog Sensors	Lutron AWN	EM Battery
Blank	Blank	Blank	Blank
8		1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
PT-BTC-6 6A Bluetooth Power Pack PT-BTN Internally Installed Low Voltage Bluetooth Node	PT-MSH-LV-MW Internally Installed Low Voltage Microwave Sensor	AWN-RF RF only Athena Wireless Node (white) Lutron Model #: A-WN- D01-RF-WH	PT-EMG-8W 8W AC EM Battery Pack PT-EMG-15W 15W AC EM Battery Pack

-	
	Add-0n ³
	EM Battery
	Blank
	PT-EMG-8W 8W AC EM Battery Pack
	PT-EMG-15W 15W AC EM Battery Pack







A-CBL-BLP-224 5' Aircraft Cable for 1x4, 2x2, 2x4

¹DOWNLOAD THE TEELIO APP







www.portorlighting.com



²TRANSFORMER

PT-SDT-325 is a step-down auto-transformer designed to convert high voltage, low current power into low voltage, high current power. It has a maximum power rating of 325VA, which makes it suitable for use in a variety of applications, such as electrical power transmission, distribution, and electronic devices.

³SOLD SEPARATELY





PT-BLP-9 Series

Back-Lit Flat Panel with Color and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Туре:

LUMEN PACKAGES

(Delivered lumens are based on the actual IES results)

CATALOG NUMBER	WATTAGE	CCT	DELIVERED LUMENS	EFFICACY (LM/W)	DLC ID
		3500K	2,984	119	
	25W	4000K	3,128	125	
		5000K	3,001	120	
PT-BLP-22-40-3CP-9	30W	3500K	3,521	117	
		4000K	3,721	124	S-1R4RPZ
		5000K	3,539	118	
		3500K	4,439	111	
	40W	4000K	4,766	119	
		5000K	4,508	113	

CATALOG NUMBER	WATTAGE	CCT	DELIVERED LUMENS	EFFICACY (LM/W)	DLC ID
_		3500K	2,984	119	
	25W	4000K	3,128	125	
		5000K	3,001	120	
		3500K	3,521	117	
PT-BLP-24-40-3CP-9	30W	4000K	3,721	124	S-JPS3Q5
		5000K	3,539	118	
		3500K	4,439	111	
	40W	4000K	4,766	119	
		5000K	4,508	113	



www.portorlighting.com

WHAT'S IN THE BOX?

Fixture

· Installation sheet








SURFACE MOUNT KIT - UNI

Surface Mount Kit for Troffer and Flat Panel

Catalog Number:	Project Name:	Note:	Date:	Туре:

DESCRIPTION


- Made of 22 ga cold rolled steel
- Painted in white after fabrication
- Easily convert recessed troffer/panel to surface mount
- Available in 2'x4', 2'x2'





SMK-UNI-24

2' x 4' Surface Mount Kit for Troffer/Flat Panel





SMK-UNI-22

2' x 2' Surface Mount Kit for Troffer/Flat Panel

SIDE VIEW FOR ALL 4.1






FLANGE KIT


White Finished Aluminum Flange Kit

Catalog Number:	Project Name:	Note:	Date:	Type:	

FK-24 2' x 4' Flange Kit



FK-22 2' x 2' Flange Kit






SURFACE MOUNT KIT - BLP

Surface Mount Kit for Flat Panel

Catalog Number:	Project Name:	Note:	Date:	Type:


LIMITED STOCK





SMK-BLP-24

2' x 4' Surface Mount Kit for Flat Panel





SMK-BLP-22

2' x 2' Surface Mount Kit for Flat Panel

SIDE VIEW FOR ALL

2.76