

PT-DLFG-R-4I-9W-3CCT

4" LED Recessed Round Floating Gimbal with Multiple CCT

Catalog Number:

DESCRIPTION

Project Name:



TUNABLE 3-1 CCT SELECTOR



With color tuning technology, and 90° tilting/360° rotating capability,

optimal for sloped ceilings, wall washing and general purpose lighting.

Portor's 4" gimbal downlights make accent, spot lighting, and wall washing so easy!

Gimbal downlights are ideal for both commercial and residential lighting, and are

Easily flip the switch for desired CCT. It's that simple!

CONSTRUCTION

Aluminum die-cast body and trim with architectural white finish. Designed for new construction, remodel or retrofit. Standard gasket included to ensure proper seal. No housing required, installs directly into the ceiling.

ELECTRICAL

Luminaire is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than traditional lamps. Low heat production requires less air-conditioning requirements, further increasing energy cost savings.

DIMMING

Triac dimmable down to 5%. Compatible with most major brands of dimmers.

LISTING

Energy Star Listed, ETL Listed, RoHS

TECHNICAL SPECIFICATION

WATTAGE	9W				
LUMENS	600 lumens				
EFFICACY	67 lm/W				
VOLTAGE	120V				
POWER FREQUENCY	50/60 Hz				
CCT	<mark>3000К 4000К 5000К</mark>				
CRI	90				
IP RATING	For damp locations				
DIMMABLE	Triac dimming				
POWER FACTOR	>0.9				
WARRANTY	5 year limited				



ORDERING SAMPLE: PT-DLFG-R-4I-9W-3CCT

Series	Watts	Lumens	Lms/Watt	CCT	CRI	Voltage
PT-DLFG-R-4I-9W-3CCT	9W	600 @4000K	67	3000K/4000K/5000K	90	120V





PT-DLFG-R-4I-9W-3CCT

4" LED Recessed Round Floating Gimbal with Multiple CCT

Catalog Number:	Project Name:	Note:	Date:	Туре:



Sealing gasket standard

MOUNTING OPTIONS



UNI-DLS 4"/6" Universal Housing for New Construction

RP-DLS-4I 4" Rough plate

QTY/CARTON



DIMENSION



