

PT-DLG-R-3I-8W-3CCT

Type:

Date:

3" LED Recessed Round Gimbal with Multiple CCT

Catalog Number:

DESCRIPTION

Project Name:

TUNABLE 3-1 CCT SELECTOR



With color tuning technology, and 30° tilting/360° rotating capability,

Gimbal downlights are ideal for both commercial and residential lighting, and optimal for sloped ceilings, wall washing and general purpose lighting.

Easily flip the switch for desired CCT. It's that simple!

CONSTRUCTION

Aluminum die-cast body and trim with architectural white finish. Designed for new construction, remodel or retrofit. Standard gasket included to ensure proper seal.

ELECTRICAL

Luminaire is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps. Low heat production requires less air-conditioning requirements, further increasing energy cost savings.

DIMMING

Triac dimmable down to 5%. Compatible with most major brands of dimmers.

LISTING

Energy Star Listed, ETL Listed, RoHS

TECHNICAL SPECIFICATION

30K 40K 50K

Note:

WATTAGE	8W			
LUMENS	600 lumens			
EFFICACY	75 lm/W			
VOLTAGE	120V			
POWER FREQUENCY	50/60 Hz			
CCT	<mark>3000К 4000К 5000К</mark>			
CRI	90			
IP RATING	For wet locations			
DIMMABLE	Triac dimming			
POWER FACTOR	>0.9			
WARRANTY	5 year limited			



ORDERING SAMPLE: PT-DLG-R-3I-8W-3CCT

Series	Watts	Lumens	Lms/Watt	CCT	CRI	Voltage
PT-DLG-R-3I-8W-3CCT	8W	600 @4000K	75	3000K/4000K/5000K	90	120V





PT-DLG-R-3I-8W-3CCT

3" LED Recessed Round Gimbal with Multiple CCT



DIMENSION



